



DELL Professional P2014H

Brand: DELL
Product code: 320-9798
Category: PC flat panels



Warranty: 3 years

49.53 cm (19.5 ") , 16:9, IPS, 1600 x 900, 250 nit, 178°/178°, LED, DVI-D, VGA, DP 1.2, 4 x UB 2.0

Bright, clear and comfortable to view.

Help boost productivity at work and enrich entertainment at home in beautiful HD with adjustable viewing features and enhanced connectivity options.

- Flexible viewing and connectivity options: Fully adjustable stand and a comprehensive set of analog and digital connectivity ports and cables.
- Excellent screen clarity: HD 1600 x 900 resolution with an ultra-wide 178°/178° viewing angle.
- Environment-conscious and reliable: Built to comply with the latest environmental and regulatory standards, and protected by a Premium Panel Guarantee and 3 years Advanced Exchange Service.

DELL P2014H, Professional. Display diagonal: 49.53 cm (19.5"), Response time: 8 ms, Display brightness: 250 cd/m². Colour of product: Black. VESA mounting interfaces: 100 x 100 mm. Input voltage: 100 - 240V, Input frequency: 50/60 Hz, Power consumption (max): 36W. EPEAT compliance: Gold, Certification: TCO <<<Less

Specs

Display		Ergonomics	
Display diagonal	49,53 cm (19.5")	Swivelling	
Response time	8 ms	Tilt adjustment	
Display brightness	250 cd/m ²	Height adjustment	
Display resolution	1600 x 900 pixels	Pivot	
Display	LED	On/off switch	
Display technology	IPS		
Display diagonal (metric)	49,4 cm		
Contrast ratio	1000:1		
		Power	
		Input voltage	100 - 240 V
		Input frequency	50/60 Hz

(typical)
 Contrast ratio (dynamic) 2000000:1
 Viewing angle, horizontal 178 °
 Viewing angle, vertical 178 °
 Display number of colours 16,77 M
 Pixel pitch 0.2712 x 0.2626 mm
 Aspect ratio 16:9

HDCP
 Supported graphics resolutions 1600 x 1200 (UXGA)

Ports & interfaces

VGA (D-Sub) ports quantity 1
 DVI port
 DVI-D ports quantity 1
 USB 2.0 ports quantity 4
 DisplayPorts quantity 1
 AC (power) in

Multimedia

Built-in camera
 TV tuner integrated

Design

Colour of product Black

Thin Client

Thin client installed

Ergonomics

Cable lock slot
 VESA mounting
 VESA mounting interfaces 100 x 100 mm

Power consumption (max) 36 W
 Power consumption (standby) 0,3 W
 Power consumption (typical) 20 W

Operational conditions

Operating temperature (T-T) 0 - 40 °C
 Storage temperature (T-T) -20 - 60 °C
 Operating relative humidity (H-H) 10 - 80 %
 Storage relative humidity (H-H) 5 - 90 %
 Non-operating altitude 0 - 12191 m
 Operating altitude 0 - 5000 m

Certificates

Energy Star certified
 EPEAT compliance Gold
 Certification TCO

Weight & dimensions

Width 47,05 cm
 Depth 4,65 cm
 Height 27,29 cm
 Weight 2,5 kg
 Package weight 6,2 kg

Packaging content

AC adapter included
 Cables included AC, DVI, USB, VGA
 Manual
 Quick start guide

[Print this data-sheet](#)

[Mail this data-sheet](#)